

Formotion INSTRUCTIONS

REV. 2007-05-23

C-Mount

PARTS LIST

Qty.	Item
1	C-Mount
1	Insert Clock
1	Hex Key
1	Countersunk socket head screw (for use with optional ELA clock and ELA thermometer)
2	Pre-installed set screws

INSTALLATION

1. Set time on clock: To access the crown remove rubber gasket. Pull out the crown and turn to set the time. Push crown back in and replace gasket to original position. Note: The inner ridge of the gasket should fit into the groove on the clock.
2. Install C-Mount on to handlebars. The C-Mount should fit snug. Remember, not all handlebars are created equal. Please avoid areas with imperfections and asymmetry.
3. Snug the pre-installed set screw using small hex key provided. **DO NOT OVERTIGHTEN!!!** If the C-Mount seems loose after tightening the set-screw, remove the C-Mount and use any type outdoor tape to fill/shim the gap(s). Retighten the set screw
4. Press Clock into C-Mount. If clock doesn't fit into the C-Mount, see step 1. You may have installed the rubber gasket incorrectly.

To activate your limited lifetime warranty and 1 year manufacturer defect warranty (see our website for details) please register your purchase at: www.FormotionProducts.com or Call Formotion Product Registration at 1-888-747-2218. You can also Fax or Mail the following information to us at:

Formotion Inc.
Product Registration
30 Liberty Ship Way STE 3110
Sausalito, CA 94965

FAX: 415-331-0440

Name _____
Address _____
City _____ State _____
Zip _____
E-Mail _____
Model(s) _____