

# Formotion INSTRUCTIONS

REV. 2007-05-23

## Clip-It!

### PARTS LIST

Qty.	Item
1	Clip-it
1	16mm socket head cap screw
2	Rubber washers
1	Chrome mounting bar (short)
1	Chrome mounting bar (long)
1	3mm Hex key

### INSTALLATION

- Loosely install the Clip-It! to the mounting bar's *non-notched* end using the screw and rubber washers, (rubber side of washers should face the mounting bar – one on each side of the mounting bar) Do not tighten down the assembly yet as you will need to adjust it later.
- The Clip-It! can be installed on either side of the mounting bar depending on your application and preference. The notched end of the bar is for attachment to the vehicle.
- Mount the assembly to the desired mounting location. (i.e. switch housing screw, windshield acorn nut, or an existing 1/4" bolt/screw)
- Adjust/rotate the Clip-It! to desired position. Ideally you should mount the Clip-It! so that the item you are clipping to it is vertical and easy to operate. Remember to feel free to increase or reduce the bend in your mount to fit your needs.
- Tighten down all screws and bolts on the entire assembly once it is in the desired location.

To activate your limited lifetime warranty and 1 year manufacturer defect warranty (see our website for details) please register your purchase at: [www.FormotionProducts.com](http://www.FormotionProducts.com) or Call Formotion Product Registration at 1-888-747-2218. You can also Fax or Mail the following information to us at:

Formotion Inc.  
Product Registration  
30 Liberty Ship Way STE 3110  
Sausalito, CA 94965

FAX: 415-331-0440

Name \_\_\_\_\_  
Address \_\_\_\_\_  
City \_\_\_\_\_ State \_\_\_\_\_  
Zip \_\_\_\_\_  
E-Mail \_\_\_\_\_  
Model(s) \_\_\_\_\_