

Formotion INSTRUCTIONS

REV. 2007-05-23

P-Clamp – Mounting Accessory

PARTS LIST

Qty.	Item
1	P-Clamp
1	25mm socket head cap screw
1	Hex Key
1	16mm socket head cap screw
1	7/8" shim ring (Not supplied with 1.25" kits)

INSTALLATION

1. Unscrew socket head cap screw using hex key provided
2. Place P-clamp in desired mounting position
3. Replace screw in countersunk hole and snug down
4. For gauges with beauty rings, (some gauge models have a chrome plate that slides over the back stem of the gauge – some models may not have this feature) install 25mm screw from the backside of the P-clamp to the gauge. For all other gauges (non-beauty ring use the shorter 16mm screw)
5. For compass installations, use the 16mm screw to attach compass directly to the long flat side of the P-clamp (note: compass must be level when the bike is in a neutral riding position and the red line should face the rider.)
6. For Clip-it installations install a rubber washer between the clip-it and P-clamp (rubber side facing Clip-it)
7. 7/8" Handlebars, use the supplied shim ring. The shim ring is not necessary for use on larger diameter bars and is not supplied with 1.25" P-Clamps.

To activate your limited lifetime warranty and 1 year manufacturer defect warranty (see our website for details) please register your purchase at: www.FormotionProducts.com or Call Formotion Product Registration at 1-888-747-2218. You can also Fax or Mail the following information to us at:

Formotion Inc.
Product Registration
30 Liberty Ship Way STE 3110
Sausalito, CA 94965

FAX: 415-331-0440

Name _____
Address _____
City _____ State _____
Zip _____
E-Mail _____
Model(s) _____