

# Formotion INSTRUCTIONS

REV. 2007-05-23

## Trigger Clock

### PARTS LIST

Qty.	Item
1	Trigger Clock
1	Socket head cap screw (already installed in trigger)
1	Hex Key

### INSTALLATION

1. Set the time: Pull out the crown turn to set time then push the crown back in
2. Unscrew socket head cap screw using hex key provided
3. Place trigger in desired location on your handlebars. Make sure that you have the correct size Trigger for your size diameter handlebars. Triggers are available for either 1" or 1.25" handlebars.
4. Replace and snug down socket head cap screw. **DO NOT OVERTIGHTEN!**
5. For 1.25" Trigger use the special shim tape provided if needed by wrapping tape around mounting location prior to installing the trigger.
6. Note: Triggers are made with a symmetrical bore but not all bars and mounting areas are perfectly cylindrical in shape. Choose a mounting area on the bar that is fairly cylindrical (most bends create imperfections and therefore are not ideal mounting locations). Most importantly, **DO NOT OVERTIGHTEN!!!**

To activate your limited lifetime warranty and 1 year manufacturer defect warranty (see our website for details) please register your purchase at: [www.FormotionProducts.com](http://www.FormotionProducts.com) or Call Formotion Product Registration at 1-888-747-2218. You can also Fax or Mail the following information to us at:

Formotion Inc.  
Product Registration  
30 Liberty Ship Way STE 3110  
Sausalito, CA 94965

FAX: 415-331-0440

Name \_\_\_\_\_  
Address \_\_\_\_\_  
City \_\_\_\_\_ State \_\_\_\_\_  
Zip \_\_\_\_\_  
E-Mail \_\_\_\_\_  
Model(s) \_\_\_\_\_